

## Displacer Type Level Switch VIPL-DLS-05

### Introduction

The displacer level switch is designed for internal mounting through the top of process vessel and is also furnished with chamber for external mounting from the process vessel. The use of displacer as the sensing medium allows for wide switching Differential, field adjustable switching point & use on high pressure applications. Mounting connection without chamber is offered in 3" flanged standard.

### Principle of Operation

Displacer operated level switch offer control featured not found in float operated controls. The Basic sensing means utilizes displacer Heavier than the liquid which is suspended from a spring. When the liquid contacts the displacer to change in turn causing the spring to seek a new balance position which moves the attraction sleeve into the field of the magnet. This Principle Provides for wide switching differential and allows the desired level switching point to be Adjusted by moving the displacers up and down the suspension cable. Further advantage Allow for adoption to high pressure application since displacers have substantial heavier Wall thickness than floats and in many cases are made out of solid materials.

### Dual Point level Switching

DLS05 Model with two displacers and two switches is designed to achieve narrow (Fixed) Differential in sequence at two different point of level. Each switch calibrated for narrow Differential and operates in sequence. Minimum upper & lower operating levels from Surface of flange are 450mm and 750mm.

### Specifications

Range	: Upto 20 meter
Min. Process Connection	: 3" flanged standard in MS/SS304/SS316/polypropylene
Differentia	: Max 70mm in S.G 1
Min. Specific Gravity	: 0.6 S.G
Pressure	: 50kg/cm <sup>2</sup> (maximum) without external chamber
Temperature	: A) SS & Teflon displacers 1500C B) Polypropylene displacers 700C
Pressure	: 100kg/cm <sup>2</sup> (maximum) with external chamber
Electric Connection	: 1/2" NPT
Displacer	: SS304/SS316/polypropylene
Switch	: SPDT/DPDT

### Accessories

Perforated still well	: CS/SS304/SS316/polypropylene & others
Size	: 65NB
External Cage	: CS/SS304/SS316/polypropylene & others
Size	: 65NB

**Installation** : Top mounting or Side mounting are the two ways of The Installation of the Displacer type Level Switch

